

Technical Data Sheet

Product Code: ACQ7730 Revised Date: 10/21/2024

Dirt Buster Kit

Product Description

Dirt Buster is an aluminum safe, high pH, multipurpose detergent engineered to attack grease, grime, soil or any other unwanted contaminants. Dirt Buster is a super concentrated chemistry capable of cleaning hard-surface, concrete shop floors & walls, industrial equipment, fleet vehicles. Dirt Buster is safe to use anywhere water is tolerable.

Performance Features

- Contains no harmful glycol ethers, phosphates, HAPs, or VOCs
- Multi-metal safe
- Package as an EZ Kit to eliminate freight costs and storage requirements

Physical Specifications

Physical State	Liquid
Appearance	Green
рН	≈12.5
Rinsability	Excellent

Equipment Requirements

Dirt Buster is safe for use with all standard cleaning equipment.

Product Make-Up

Dirt Buster is the concentrated version of Seacole's Total. Packaged as an EZ Kit with two parts. When both parts are combined Dirt Buster can be diluted with water to make 30 gallons of Seacole's Total. Dirt Buster must be diluted with water prior to use.

Concentration and Application Method

Dilutions Requirements

Dirt Buster must first be diluted with water prior to use. Mix equal amounts of Part A and Part B together with 25 gallons of water. This solutions can then be used at different concentrations depending on application.

General Maintenance

Use Dirt Buster at a use concentration of 3%-20% by volume depending on the nature, make-up and extent of the soils to be removed. The use of HOT water increases performance. Apply to the surface to be cleaned with the desired application method. Follow with a thorough water rinse.

Mop/Bucket

For heavy duty shop floor cleaning, add 10%–20% by volume of Dirt Buster to a mop bucket filled with HOT clean water. Apply to the surface to be cleaned with mop or brush. Where soil deposits are heavy, let soak for 5 to 15 minutes and brush if possible. Follow with additional mopping or a thorough hose or high- pressure water rinse. For additional soil removal, wet-vacuum dry-cleaned area. Automatic Floor Scrubbers

For heavy duty shop floor & hard surface cleaning, add 10%–20% by volume of Dirt Buster to the already water filled solution tank. Adding Dirt Buster to the tank after filling with water will diminish foam production. Hot water temperatures for most plastic-tanked scrubbers should not exceed 140° F. Where soil deposits are heavy, a double pass may be necessary. Rinse with clean water. Operation of equipment should be done in accordance with the equipment manufacturer's instructions. Sponge/Bucket Vehicle Washing



+1 (763) 582-1140 | **+1 (800) 966-2909** | 13505 Industrial Park Blvd. Plymouth, MN 55441 |







Technical Data Sheet

For typical vehicle, truck or fleet washing, add 5%-10% by volume of Dirt Buster to a water-filled bucket at a temperature between 40°-160° F. Apply to surface to be cleaned with sponge or brush. Where soil deposits are heavy, let soak for 5–15 minutes and brush if possible. Follow with a thorough hose or high-pressure water rinse.

Low- or High-pressure Washer

Apply Dirt Buster at a rate of 4–12 fl. ounces/gallon (ratios of 1:32–1:10). Apply to surface to be cleaned. Where soil deposits are heavy, let soak for 5–15 minutes and brush if possible. Follow with a thorough hose or high-pressure water rinse. Foaming Equipment

Dirt Buster will create high quality foam through typical low- & high-pressure foam generators. Apply to surface to be cleaned. Allow foam to soak and cling to soils. Where soil deposits are heavy, let soak for 5–15 minutes and brush if possible. Follow with a thorough hose or high-pressure water rinse. Chemical set-up and operation of equipment should be done in accordance with the equipment manufacturer's instructions.

Companion Products

For the nonconcentrated version of this product please see Seacole's Total. Please see Seacole Product Catalog.

Safety and Handling

Please review and understand the Dirt Buster SDS before handling.

Waste Treatment

Individual users should verify the nature of spent solutions to assure compliance with local, state, and federal regulations.

Ordering Information

Dirt Buster is available as an EZ Kit containing 2 parts each packaged in either: 2.5-gallon jug, 5-gallon pails, 55-gallon drums, or 275-gallon totes.







